

DC POWER SUPPLY

CODE 9914-BP506

- Four-digit LED display
- Independent voltage and current control knob
- Output switch control
- Panel locking function to prevent misoperation
- USB interface for power supply
- OVP/OCP protection
- 3 shortcut keys for presetting



SPECIFICATION

Rate output voltage	0~50V	
Rate output current	0~6A	
Maximum output power	150W	
Voltage	setting resolution	10mV
	setting accuracy	$\leq 0.5\% + 50mV$
	readback resolution	10mV
	readback accuracy	$\leq 0.5\% + 50mV$
	load regulation	$\leq 0.05\% + 5mV$
	line regulation	$\leq 0.1\% + 3mV$
	ripple	$\leq 5mV_{rms}$
Current	setting resolution	1mA
	setting accuracy	$\leq 0.5\% + 5mA$
	readback resolution	1mA
	readback accuracy	$\leq 0.5\% + 5mA$
	load regulation	$\leq 0.1\% + 3mA$
	line regulation	$\leq 0.1\% + 3mA$
	ripple	$\leq 20mArms$
OVP	0~55V	
OCP	0~6.5A	
Work condition	temperature: 0°C~40°C, humidity: $\leq 75\%RH$	
Storage condition	temperature: -20°C~50°C, humidity: $\leq 90\%RH$	
Cool system	fan cool	
Power supply	110V/220V±10%, 50Hz/60Hz	
Dimension	200x80x155mm	
Weight	1.23kg	

STANDARD DELIVERY

Main unit	1 pc
Test lead	2 pcs