

HOLLOW RATCHET MECHANICAL TORQUE WRENCHES

- Ratchet head is more durable
- According to DIN ISO 6789, ASME B107.300
- Hollow square tenon up/down switching, accommodates clockwise/counter-clockwise operation
- Dual window design with clear scale
- Non-slip grip handle
- Push-pull locking device, easy to operate



IST-43WM100

SPECIFICATION

Code	Range	Accuracy	Graduation	Square driver (D)	Length	Net weight
IST-43WM25	5~25N.m	±3%	0.2N.m	1/4"	328mm	840g
IST-43WM50	10~50N.m		0.5N.m	3/8"	392mm	1000g
IST-43WM60	10~60N.m		0.5N.m	3/8"	392mm	1000g
IST-43WM100	20~100N.m		0.5N.m	1/2"	434mm	1100g
IST-43WM150	30~150N.m		1N.m	1/2"	504mm	1250g
IST-43WM200	40~200N.m		1N.m	1/2"	504mm	1250g
IST-43WM300	60~300N.m		1.5N.m	1/2"	556mm	1400g
IST-43WM400	80~400N.m		2N.m	1/2"	700mm	1970g
IST-43WM550	100~550N.m	±3% (≤500N.m) ±4% (>500N.m)	3N.m	3/4"	924mm	3670g
IST-43WM750	150~750N.m		5N.m	3/4"	1076mm	4100g
IST-43WM850	200~850N.m		5N.m	3/4"	1207mm	4500g
IST-43WM1000	200~1000N.m		5N.m	3/4"	1207mm	4670g
IST-43WM1500	300~1500N.m		10N.m	1"	1765mm	6500g
IST-43WM2000	400~2000N.m		10N.m	1"	1943mm	6800g